



GH-1440-1 Lathe with Newall NMS300 DRO

Product Images



Short Description

GH-1440-1 Lathe with Newall DP500 DRO

Additional Information

Stock Number	JT9-323386
Carriage Travel (In.)	37-1/2
Compound Slide Travel (In.)	3-1/2
Length of Gap (In.)	9-3/8
Max Tool Size (In.)	5/8 x 5/8
Model Number	GH-1440-1
Motor (HP)	3HP, 230V, 1PH
Number of Inch Threads	40.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	23.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	74-4/5 x 28 x 46
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0004 - 0.0103
Range of Inch Threads (TPI)	4-112
Range of Longitudinal Feeds (IPR)	0.0012 - 0.0294
Range of Metric Threads	0.45-7.5
Range of Spindle Speeds (RPM)	40-1800
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	3-1/2
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	8-1/5

Swing Through Gap (In.)	20
Tailstock Spindle Travel (In.)	4-3/4
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	2336
Width of Bed (In.)	10-1/5

