



# GH-1660ZX With ACU-RITE 303 DRO

## Product Images

---



## Short Description

---

GH-1660ZX With ACU-RITE 303 DRO

## Additional Information

|                                             |                              |
|---------------------------------------------|------------------------------|
| Stock Number                                | JT9-321388                   |
| Carriage Travel (In.)                       | 55-9/16                      |
| Compound Slide Travel (In.)                 | 5-1/8                        |
| Cross Slide Travel (In.)                    | 9                            |
| Drive                                       | Geared Head                  |
| Length of Gap (In.)                         | 12                           |
| Max Tool Size (In.)                         | 1 x 1                        |
| Model Number                                | GH-1660ZX                    |
| Motor (HP)                                  | 7-1/2 HP, 230/460, 3 Ph      |
| Number of Inch Threads                      | 61.0000                      |
| Number of Longitudinal and Cross Feed Rates | 46/31                        |
| Number of Metric Threads                    | 24.0000                      |
| Number of Spindle Speeds                    | 12                           |
| Overall Dimensions (L x W x H) (In.)        | 115 x 44 x 66                |
| Prop 65                                     | Cancer and Reproductive Harm |
| Range of Cross Feeds (IPR)                  | .0006 - .0360                |
| Range of Inch Threads (TPI)                 | 1-5/8 - 72                   |
| Range of Longitudinal Feeds (IPR)           | .0015 - .0900                |
| Range of Metric Threads                     | .05 - 20                     |
| Range of Spindle Speeds (RPM)               | 25 - 1,800                   |
| Size                                        | 16 x 60                      |
| Spindle Bore (In.)                          | 3-1/8                        |
| Spindle Mount                               | D1-8                         |
| Spindle Taper with Sleeve                   | MT-7 (MT-5)                  |

|                                |                             |
|--------------------------------|-----------------------------|
| Steady Rest Capacity (In.)     | 3/8 - 7                     |
| Style (Type)                   | Engine - Large Spindle Bore |
| Swing Over Bed (In.)           | 16                          |
| Swing Over Cross Slide (In.)   | 10                          |
| Swing Through Gap (In.)        | 25-1/2                      |
| Tailstock Spindle Travel (In.) | 5                           |
| Weight (Lbs.)                  | 5795                        |
| Width of Bed (In.)             | 13-3/8                      |

