



# GH-26120ZH With Newall DP700 DRO

## Product Images

---



## Short Description

---

GH-26120ZH With Newall DP700 DRO

## Additional Information

|                                             |                                               |
|---------------------------------------------|-----------------------------------------------|
| Stock Number                                | JT9-321891                                    |
| Carriage Travel (In.)                       | 108-1/4                                       |
| Compound Slide Travel (In.)                 | 5-1/2                                         |
| Drive                                       | Geared Head                                   |
| Length of Gap (In.)                         | 8                                             |
| Max Tool Size (In.)                         | 1-1/4 x 1-1/4                                 |
| Model Number                                | GH-26120ZH                                    |
| Motor (HP)                                  | 10 HP, 230/460, 3 Ph                          |
| Number of Inch Threads                      | 48.0000                                       |
| Number of Longitudinal and Cross Feed Rates | 65                                            |
| Number of Metric Threads                    | 22.0000                                       |
| Number of Spindle Speeds                    | 12                                            |
| Overall Dimensions (L x W x H) (In.)        | 178 x 43 x 57                                 |
| Prop 65                                     | Cancer and Reproductive Harm                  |
| Range of Cross Feeds (IPR)                  | .0040 - .0404                                 |
| Range of Inch Threads (TPI)                 | 2-30                                          |
| Range of Longitudinal Feeds (IPR)           | .0023 - .0937                                 |
| Range of Metric Threads                     | 1 - 14                                        |
| Range of Spindle Speeds (RPM)               | 36 - 1,600                                    |
| Size                                        | 26 x 120                                      |
| Spindle Bore (In.)                          | 4-1/8                                         |
| Spindle Mount                               | D1-8                                          |
| Spindle Taper with Sleeve                   | MT-5                                          |
| Steady Rest Capacity (In.)                  | Small 25/32 - 4-29/32, Large 3-15/16 - 9-7/16 |

| Style (Type)                   | Engine - Large Spindle Bore |
|--------------------------------|-----------------------------|
| Swing Over Bed (In.)           | 26                          |
| Swing Over Cross Slide (In.)   | 16-1/2                      |
| Swing Through Gap (In.)        | 34                          |
| Tailstock Spindle Travel (In.) | 6                           |
| Taper in Tailstock Spindle     | MT-5                        |
| Weight (Lbs.)                  | 9362                        |
| Width of Bed (In.)             | 16                          |

